Marley V Tech Adiabatic Fluid Cooler

The Marley V Tech Adiabatic Fluid Cooler enhances the utility of an air cooled system with the efficiency boost of a wet system during peak conditions, providing lower energy usage and smaller footprint than an air cooled fluid cooler and lower site water usage than an evaporative fluid cooler.

Features and Benefits

Integral energy management system
 monitors and regulates fan speed
 Maintenance free EC motors ensure reliable and efficient operation



Applications	Fluid Cooling
Capacity	36 – 871 gpm Water, 100°F Inlet - 90°F Outlet, 95° F DB / 78° F WB
Unit Sizes	1 – 18 fans
Air Flow	Induced draft, vertical discharge
Fans	Direct drive airfoil impellers
Motors	Electronically commutated (ECM): 2.4 kW - 3.7kW
Nominal Width	4 ft – 8 ft
Nominal Length	4 ft – 38 ft
Nominal Height	5.7 ft – 9.4 ft
Coil Construction	Copper tube/aluminum fin - Epoxy coated fin option
Rigging	Built-in lifting eyes
Mounting	Heavy-duty rigid foot mount

ENERGY AND WATER MANAGEMENT CONTROL SYSTEM

- Plug and play system with automatic motor programming
- Adaptave water flow control
- Standalone or remote interface control

- Setpoint changeover and/or nighttime limiter
- Operational and fault signaling
- Remote monitoring
- Bypass operation

WATER DISTRIBUTION SYSTEM

The system provides even water distribution across the entire surface area of the cooling pads to minimize dry spots. The pad's fluted angles direct water flow towards the air inlet side of the pad where most evaporation takes place.

A targeted amount of water is not evaporated, helping to continuously rinse the pads, minimizing scaling and clogging of the inlet from atmospheric dust. This also minimizes the accumulation of dirt on the finned surface area of the heat exchanger.

The Marley V Tech System's highly-engineered metered water distribution system minimizes water treatment requirements.



7401 WEST 129 STREET

OVERLAND PARK, KS 66213 USA
913 664 7400 | spxcooling@spx.com

spxcooling.com



